

50 Hz RANGE

Model Name	Standby Ratings		Prime Ratings		Engine Model	Standard Alternator	Standard Controller	EU Stage	Sound Enclosure
	kVA	kWe	kVA	kWe					
C8 D5	8.25	6.6	7.5	6	X1.3G2	PI044D	PS0500		STD
C11 D5	11	8.8	10	8	X1.3G2	PI044E	PS0500		STD
C17 D5	16.5	13	15	12	X2.5G2	PI044G	PS0500		●
C22 D5	22	17	20	16	X2.5G2	PI144D	PS0500		●
C28 D5	27.5	22	25	20	X2.5G2	PI144F	PS0500		●
C33 D5	33	26.4	30	24	X3.3G1	PI144G	1.1		●
C38 D5	38	30.4	35	28	X3.3G1	PI144H	1.1		●
C44 D5	44	35	40	32	S3.8G4	UCI224C	PS0500		●
C55 D5	55	44	50	40	S3.8G6	UCI224D	PS0500		●
C66 D5	66	52	60	48	S3.8G7	UCI224F	PS0500		●
C44 D5e	44	35.2	40	32	4BT3.3G3	UCI224C	1.1	II	●
C55 D5e	55	44	50	40	4BT3.3G3	UCI224D	1.1	II	●
C90 D5	90	72	82	65	6BTA5.9G5	UCI224G	1.2		●
C110 D5	110	88	100	80	6BTA5.9G5	UCI274C	1.2		●
C150 D5	150	120	136	109	6BTA5.9G2	UCI274E	1301		●
C175 D5e	175	140	158	126	QSB7G5	UCI274F	1.2	IIIA	●
C200 D5e	200	160	182	146	QSB7G5	UCI274H	1.2	IIIA	●
C220 D5e	220	176	200	160	QSB7G5	UCI274H	1.2	IIIA	●
C250 D5	250	200	227	182	6CTAA8.3G2	UCDI274J	1301	4g	●
C275 D5	275	220	250	200	QSL9G5	UCDI274K	1.2	4g	●
C300 D5	300	240	275	220	QSL9G5	HCI4D	1.2	4g	●
C330 D5	330	264	300	240	QSL9G5	HCI4D	1.2	4g	●
C350 D5	350	280	320	256	NT855G6	HCI4E	2100		●
C400 D5	400	320	360	288	NTA855G4	HCI4F	2100		●
C440 D5	440	352	400	320	NTA855G7	HCI5C	2100		●
C400 D5e	400	320	364	291.2	QSX15G8	HCI4F	2.2	II	●
C450 D5e	450	360	409	327.2	QSX15G8	HCI5C	2.2	II	●
C500 D5e	500	400	455	364	QSX15G8	HCI5C	2.2	II	●
C550 D5e	550	440	500	400	QSX15G8	HCI5D	2.2	II	●
C700 D5	706	565	640	512	VTA28G5	HCI5F	3.3		ISO20
C825 D5A	825	660	750	600	VTA28G6	HCI6G	3.3		ISO20
C825 D5	825	660	750	600	QSK23G3	HCI6G	2100		x
C900 D5	900	720	820	656	QSK23G3	HCI6H	2100		x
C1000 D5	1041	832.8	939	751.2	QST30G3	HCI6J	3.3		ISO20
C1100 D5	1110	888	1000	800	QST30G4	HCI6K	3.3		x
C1100 D5B	1132	906	1029	823	KTA38G5	HCI6K	3.3		HC40
C1400 D5	1400	1120	1250	1000	KTA50G3	PI734B	3.3		HC40
C1675 D5	1675	1340	1400	1120	KTA50G8	PI734D	3.3		HC40
C1675 D5A	1675	1340	1500	1200	KTA50GS8	PI734D	3.3		HC40
C1760 D5e	1760	1408	1600	1280	QSK60GS3	PI734D	3201	2g	x
C2000 D5e	2000	1600	1825	1460	QSK60GS3	PI734F	3201	2g	x
C2000 D5	2063	1650	1875	1500	QSK60G3	PI734F	3201		x
C2250 D5	2250	1800	2000	1600	QSK60G4	PI734G	3201		x
C2500 D5A	2500	2000	2250	1800	QSK60G8	LVS1804S	3201		x
C2750 D5	2750	2200	2500	2000	QSK78G9	LVS1804R	3.3		x
C3000 D5	3000	2400	2750	2200	QSK78G9	LVS1804S	3.3		x
C3300 D5	3325	2660	3000	2400	QSK78G6	LVS1824G	3201		x

60 Hz Range overleaf

60 Hz RANGE

Model Name	Standby Ratings		Prime Ratings		Engine Model	Standard Alternator	Standard Controller	EPA Cert.	Sound Enclosure
	kVA	kWe	kVA	kWe					
C12 D6	15	12	13	11	X2.5G4	PI044F	PS0500		●
C16 D6	20	16	18	15	X2.5G4	PI044H	PS0500		●
C20 D6	25	20	22	18	X2.5G4	PI144D	PS0500		●
C30 D6	37.5	30	33.8	27	X3.3G2	PI144G	1.1		●
C35 D6	43.8	35	40	32	X3.3G2	PI144H	1.1		●
C40 D6	50	40	45	36	S3.8 G8	UCI224C	PS0500		●
C50 D6	62	50	56	45	S3.8 G9	UCI224D	PS0500		●
C60 D6	75	60	67	54	S3.8 G10	UCI224E	PS0500		●
C40 D6	50	40	45	36	4BT3.3G3	UCI224C	1.1		●
C50 D6	62.5	50	56.3	45	4BT3.3G3	UCI224D	1.1		●
C80 D6	100	80	90	72	6BTA5.9G6	UCI224G	1.2		●
C100 D6	125	100	114	91	6BTA5.9G6	UCI274C	1.2		●
C135 D6	169	135	153	122	6BTA5.9G2	UCI224F	1301		●
C150 D6e	188	150	169	135	QSB7G5	UCI274F	1.2	T3	●
C175 D6e	218	175	200	160	QSB7G5	UCI274H	1.2	T3	●
C200 D6e	250	200	225	180	QSB7G5	UCI274H	1.2	T3	●
C225 D6	281	225	256	205	6CTAA8.3G2	UCDI274J	1301		●
C250 D6	313	250	282	225	QSL9G5	UCDI274K	1.2		●
C275 D6	344	275	313	250	QSL9G5	HCI4D	1.2		●
C300 D6	375	300	344	275	QSL9G5	HCI4D	1.2		●
C350 D6	438	350	400	320	NTA855G3	HCI4F	2100		●
C400 D6	500	400	456	365	NTA855G5	HCI5C	2100		●
C450 D6e	562	450	511	409	QSX15G9	HCI5C	2.2	T2	●
C500 D6e	625	500	568	455	QSX15G9	HCI5D	2.2	T2	●
C600 D6	754	603	681	545	VTA28G5	HCI5F	3.3		ISO20
C750 D6	938	750	850	680	QSK23G3	HCI6H	2100		x
C800 D6	1000	800	906	725	QSK23G3	HCI6H	2100		x
C900 D6	1156	925	1044	835	QST30G3	HCI6J	3.3		ISO20
C1000 D6	1265	1012	1150	920	QST30G4	HCI6K	3.3		x
C1000 D6B	1276	1020	1160	928	KTA38G4	HCI6K	3.3		HC40
C1250 D6	1588	1270	1400	1120	KTA50G3	PI734B	3.3		HC40
C1500 D6	1931	1545	1608	1286	KTA50G9	PI734C	3.3		HC40
C2000 D6	2500	2000	2281	1825	QSK60G6	PI734F	3201		x
C2250 D6A	2813	2250	NA	NA	QSK60G9	PI734G	3201		x
2500 DQLC	3125	2500	2920	2336	QSK78G6	LVS1804R	3201		x
2750 DQLD	3438	2750	3125	2500	QSK78G8	LVS1804S	3201		x

For Rating Definitions refer to Data Sheet.

Cummins Power Generation Limited
 Manston Park, Columbus Avenue
 Manston, Ramsgate, Kent CT12 5BF, UK
 Telephone: +44 (0)1843 255000. Fax: +44 (0)1843 255902
 Email: cpg.uk@cummins.com
www.cumminspower.com www.cummins.com

See your distributor for more information.